



## K30L AIR COMPRESSOR – 415V THREE PHASE

PISTON DISPLACEMENT (to AS4637)	871.8 L/MIN ~ 30.8 CFM
FREE AIR DELIVERY (to AS4637)	681 L/MIN ~ 24.1 CFM
MAXIMUM CUT OUT PRESSURE	1100 KPA ~ 160 PSI
COMPRESSOR PUMP	TWIN CYLINDER, TWO STAGE, ITALIAN MADE
MOTOR	5.0 KW ~ 7.5 HP 415V THREE PHASE 50HZ <b>NOTE: NOT SUPPLIED WITH LEAD &amp; PLUG</b>
REQUIRED CIRCUIT BREAKER	25 AMP **
RECEIVER	267 LITRE (STATIC), TO AS1210, AUSTRALIAN MADE
DIMENSIONS	1770mm L X 600mm W X 1130mm H
WEIGHT	200 KG*
AIR OUTLET	3/4" BSP

\* APPROX ONLY

\*\* INDICATIVE ONLY, PLEASE CHECK WITH YOUR ELECTRICIAN



### FEATURES

- AUSTRALIAN DESIGNED AND BUILT
- INDUSTRIAL GRADE HAMMERTONE ENAMEL FINISH
- CAST IRON CYLINDER PUMP
- ELECTRIC MOTOR OVERLOAD
- WARRANTY: 3 YEARS ON PUMP, 1 YEAR ON ALL OTHER COMPONENTS

[www.pilotair.com.au](http://www.pilotair.com.au)  
[sales@pilotair.com.au](mailto:sales@pilotair.com.au)